

## 3 dB Hybrid Coupler RK3-588P-6G-L

MTS-No.: 25836

### Description

The 3 dB Hybrid Couplers of this series are designed to work at frequency ranges between 700 MHz and 6000 MHz. They cover for example GSM, DECT, UMTS, Bluetooth, WiMAX, Wi-Fi (2.4G / 5G) and all LTE frequency bands.

The multisection stripline design exhibits good flatness and VSWR at all ports.



### Technical data:

#### 1 RF-specifications:

1.1 Coupler type	RK3, 3 dB		
1.2 Impedance	50 $\Omega$		
1.3 Input power	100 W max.		
1.4 Frequency range	700 - 6000 MHz		
	<b>min.</b>	<b>typ.</b>	<b>max.</b>
1.5 VSWR (at all ports)		1.25	1.6
1.6 Insertion loss / Coupling (+3 dB)		0.4 dB	0.9 dB
1.7 Isolation	14 dB	20 dB	
1.8 Amplitude balance			
@ 900 - 6000 MHz		$\pm 0.3$ dB	$\pm 0.7$ dB
@ 700 - 900 MHz		$\pm 0.8$ dB	$\pm 1.7$ dB
1.9 Phase balance (90°)		$\pm 1^\circ$	$\pm 4^\circ$

#### 2 Connections:

2.1 RF-in- and outputs	4x N female (4x SMA female available @ MTS-No.: 25835)
------------------------	--

#### 3 General specifications:

3.1 Operating temperature	-55 °C - +75 °C
3.2 Reference temperature for specifications	+25 °C
3.3 Dimensions (without connections)	68.4 mm x 50 mm x 22 mm (LxWxH)
3.4 Case style	Milled aluminium enclosure
3.5 Colour	SurTec650 (Chrome alloy)
3.6 Weight	230 grams

#### 4 Delivered parts:


RK3-588P-6G-L  
Datasheet

#### 5 Comments:

Warranty	12 months
RoHS-compliant	Yes

#### 6 Recommended accessories:

RF-cables  
Attenuators series PAH



### 3 dB Hybrid Coupler RK3-588P-6G-L

MTS-No.: 25836

#### Typical measurements:




Fig. 1: Through and coupled line insertion loss




Fig. 2: Isolation between output ports




Fig. 3: VSWR at all ports




Fig. 4: Amplitude balance between output ports





Fig. 5: Phase balance between output ports



### 3 dB Hybrid Coupler RK3-588P-6G-L

MTS-No.: 25836

#### Port configuration:

Input	IN	ISO	-3 dB / 0°	-3 dB / -90°
IN	---	ISOLATION	-3 dB / 0°	-3 dB / -90°
ISO	ISOLATION	---	-3 dB / -90°	-3 dB / 0°
-3 dB / 0°	-3 dB / 0°	-3 dB / -90°	---	ISOLATION
-3 dB / -90°	-3 dB / -90°	-3 dB / 0°	ISOLATION	---

#### Views:

