

Relay Switching Unit KRE-4170-ESMIL

MTS-No.: 31071

Page 1 from 3

Application

The Relay Switching Unit series KRE-4000 can be used for several applications, f.e.:

- Switching Unit for RF-generators, amplifiers and antennas at EMC test laboratories
- RF matrix
- Filter, diplexer attenuator etc. selection unit
- Any automated routing of measurement equipment at test benches

Description

The Relay Switching Unit series KRE-4000 is for the switching of almost every kind of signals. Due to the modular design, the electrical characteristics of the switches can be adapted to versatile demands. In combination with attenuators, splitters and other modules the usability can be extended.



Characteristics

- ▶ Configuration:
3x SP6T relay (R573.803.610 Radiall)
- ▶ Integrated power supply 100 V - 240 V AC
- ▶ Manual control (colour display with touchpanel)
- ▶ Remote control by USB, LAN and IEEE-488 (other interfaces web control on request)
- ▶ 19" rack mount case with 3 HU
- ▶ Windows control programs can be offered
- ▶ High quality materials and components for extended durability
- ▶ On request user blocking of separate components (with name / name and keyword available)
- ▶ On request switching cycles of every relay position can be requested
- ▶ Relay Switching Units can be designed according to customer's individual requirements

Relay Switching Unit KRE-4170-ESMIL

MTS-No.: 31071

Page 2 from 3

Configuration:

3x SP6T relay (R573.803.610 Radiall)

Technical data:

1 RF-specifications relays:

1.1 Relay type (relays 1 - 3)	SP6T relay (R573.803.610 Radiall)	
1.2 Impedance	50 Ω	
1.3 RF-power max. (throughput power)	40 W CW @ 6.0 GHz (*) 30 W CW @ 12.4 GHz (*) 25 W CW @ 18.0 GHz (*) 15 W CW @ 26.5 GHz (*) 5 W CW @ 40.0 GHz (*)	
1.4 Frequency range	DC – 40.0 GHz	
1.5 RF-connections	SMA2.9 female	
1.6 Switching time max.	15 ms	
1.7 Operating life min.	2 000 000 cycles	
1.8 VSWR max.	DC – 6.0 GHz	1.30 : 1
	DC – 12.4 GHz	1.40 : 1
	DC – 18.0 GHz	1.50 : 1
	DC – 26.5 GHz	1.70 : 1
	DC – 40.0 GHz	2.20 : 1
1.9 Isolation min.	DC – 6.0 GHz	70 dB
	DC – 12.4 GHz	60 dB
	DC – 18.0 GHz	60 dB
	DC – 26.5 GHz	55 dB
	DC – 40.0 GHz	50 dB
1.10 Insertion loss max.	DC – 6.0 GHz	0.20 dB
	DC – 12.4 GHz	0.40 dB
	DC – 18.0 GHz	0.50 dB
	DC – 26.5 GHz	0.70 dB
	DC – 40.0 GHz	1.10 dB

2 Connections:

2.1 Front side	Power switch with integrated control lamp Colour display with touchpanel
2.2 Rear side	RF-connections Control card with control interfaces Appliance plug with the integrated fuses F1 and F2 Ground connector

3 General specifications:

3.1 Power supply	100 V - 240 V 50 Hz / 60 Hz
3.2 Internal voltage	+5 V DC, +28 V DC
3.3 Control displays	Control lamp in the power switch Colour display with touchpanel
3.4 Control interfaces	USB LAN IEEE-488
3.5 Power consumption primarily	150 mA max. @ 230 V (no relay switched) 200 mA max. @ 230 V (all relays switched)
3.6 Voltage supply	Standard rubber connector
3.7 Operating temperature	0 °C - +50 °C
3.8 Reference temperature for specifications	+25 °C
3.9 Dimensions	19"-unit x 3 HU x 310 mm (dimensions without handles and connections)
3.10 Colour	Front side colourless anodized Rear side colourless anodized
3.11 Weight	6.6 kg

4 Delivered parts:

KRE-4170-ESMIL
Power cable
CD with operating manual

5 Comments:

Warranty 12 months
RoHS-compliant Yes

6 Recommended accessories:

RF-cables
Terminations
Attenuators

(*) Non-switching. The maximum RF-power is shortened depending on present standing waves. Please consult derating factors of the relay manufacturer and consult the specification of used RF connectors.

31071.SPEC / KRE-4170-ESMIL / 11 January 2024

© MTS Systemtechnik GmbH
Technical subject to change

Relay Switching Unit KRE-4170-ESMIL

MTS-No.: 31071

Page 3 from 3

Views:

